

Facility Name: Oak Tree Landing Airport		Inspection Date: 4/9/2026	
Facility Type: Airport		Status: Active	
Inspector: David Smith			
Location ID: 6J8	FAA Site No.: 03230.1*A	FDOT District: 2	
7.00 Miles SW of High Springs		County: Alachua	
ARP Latitude: 29° 43' 12.95	Source: Estimated	Ownership: Private	
ARP Longitude: 82° 39' 54.75		Use: Public	
Elevation: 90	Source: Estimated	Sectional Chart: JACKSONVILLE	

Note: Primary contact shows below with a background.

Facility Owner: HLT Gilchrist, LLC	Facility Physical Address
Address: 25755 NW 130th Av	Address: 1400 SE 80th Av
City: High Springs State: FL ZIP: 32643	City: Newberry State: FL ZIP: 32669
Phone: (386) 454-1511 Fax:	Phone: (386) 454-1511
Email: info@loncala.com	
Owner Representative:	Facility Manager: Wesley Carter
Address:	Address: 25755 NW 130th Av
City: State: ZIP:	City: High Springs State: FL ZIP: 32643
Phone:	Phone: (352) 538-7575
Email:	Email: wesley@loncala.com

Acres: 70 Residential Airpark: No	Beacon:
Section: 07 Township: 09S Range: 17E	Wind Indicator: Yes Lighted: Yes
Lighting Schedule:	Notes:
Attendance Schedule: Month/Day/Hour	Segmented Circle: No Lighted: No
	Facility Website:
	Ask in any new facility aeriels/photos are available

Based Aircraft				
Year: 2010	Single Engine:	Jet Engine:	Glider:	Ultralight:
Source: Inspector	Multi Engine:	Helicopter:	Military:	Seaplane:
Total Based Aircraft:				

Annual Operations			
Year:	Air Carrier:	Air Taxi:	GA Local:
End Date:	Commuter:	Military:	GA Itinerant:
Total Annual Operations:			

FAR 139 Certificated

FAA NavCom	
FSS ID: ☒ GNV	Clearance Delivery: ☐
FSS on Airport: ☒ No	Ground Control: ☐
Toll Free: ☒ (800) WX-BRIEF	Control Tower: ☐
VorTac: ☐	Approach Control: ☐
AWOS/ASOS: ☐	Unicom: ☐
Instrument Approach: ☐	ATIS: ☐
	CTAF: ☒ 122.900

Facility Name: Oak Tree Landing Airport

Inspection Date: 4/9/2026

Facility Type: Airport

Status: Active

Inspector: David Smith

Services

Fuel:

A ☐
 A1 ☐
 A1+ ☐
 B ☐
 B+ ☐
 Diesel ☐
 E85 ☐
 G100UL ☐
 Mogas ☐
 SAF ☐
 UL102 ☐
 80 ☐
 85UL ☐
 87 ☐
 91/96 ☐
 91/96UL ☐
 100 ☐
 100LL ☐
 100VLL ☐
 115 ☐

Bottle Oxygen:

High ☐
 Low ☐

Bulk Oxygen:

High ☐
 Low ☐

Transient Storage:

Buoy ☐
 Hangar ☐
 Tie Downs ☐

Airframe:

Major ☐
 Minor ☐

Power Plant:

Major ☐
 Minor ☐

Other Services:

Aerial Surveying ☐
 Air Ambulance ☐
 Air Freight ☐
 Aircraft Rental ☐
 Aircraft Sales ☐
 Avionics ☐
 Beaching Gear ☐
 Car Rental ☐
 Cargo ☐
 Courtesy Car ☐
 Charter ☐
 Crop Dusting ☐
 Glider ☐
 Glider Towing ☐
 Instruction ☐
 Internet ☒
 Lodging ☐
 Parachute Jumping Area ☐
 Restaurant ☐
 Restrooms ☒
 Taxi ☐
 Telephone ☒ 911

Aircraft Charging Stations:

Electric Charging Stations ☐
 Hydrogen Charging Stations ☐
 Battery Charging Stations ☐
 Solar Charging Stations ☐
 Auto Charging Stations ☐

Aircraft Electric Charging Power Rating:

Alternating Current ☐
 Direct Current ☐

Aircraft Electric Charging Station Plug Type

AC - J1772 ☐
 AC - Mennekes ☐
 DC - GB/T ☐
 DC - CCS Type1 ☐
 DC - CCS Type2 ☐
 DC - MCS ☐
 DC - CHAdeMO ☐
 Other ☐

Support Infrastructure:

Passenger Waiting Facility ☐
 Aircraft Tug Station ☐
 Deicing Equipment ☐
 Battery Thermal Conditioning System ☐
 Maintenance Platforms, Ladders, Inspection ☐
 Provider of Services ☐
 Fire Suppression/Extinguishing System ☐
 Aircraft Cabin Thermal Conditioning Equipment ☐
 Passenger/Cargo Loading Equipment ☐

Aircraft Electric Charger Power Output:

Number of Aircraft Electric Charging Stations:

Facility Name: Oak Tree Landing Airport				Inspection Date: 4/9/2026	
Facility Type: Airport		Status: Active		Inspector: David Smith	
Runway ID	Status	Dimension	Surface	Condition	Lights
09/27	Existing	4,637 x 75	Asph	Good	None

Comments:

RWY 09**FAR 77 Category A(V)****RWY 27****FAR 77 Category A(V)**

Approach ratio required is RWY 09 20:1 and RWY 27 20:1.

Primary surface required is 250 feet wide.

Transitional surface required is 0:1.

Safety area required extends 240 feet beyond each runway end.

Runway 09

	Latitude	Longitude	Source	Slope	Marking	VGSI	REIL	Rt Traffic	Approach
09	29° 43' 12.70	82° 40' 21.05	Estimated	6:1	NPI-P	N	No	No	NONE

Obstruction Data

	Close-in Obstruction	Displacement Distance	Slope	Controlling Obstruction	Marked/ Lighted	Height Above Runway	Distance From Runway	Direction From Runway End	Controllin g Offset
Primary Surface	No		6:1	ROAD		22 ft	343 ft	Before Runway End	0 ft Both
Runway End	No		15:1	TREES		24 ft	368 ft	Before Runway End	120 ft R
Marked Displaced Threshold	No	100 ft	20:1	TREES		24 ft	368 ft	Before Runway End	120 ft R
Required Displaced Threshold									

Runway 27

	Latitude	Longitude	Source	Slope	Marking	VGSI	REIL	Rt Traffic	Approach
27	29° 43' 13.13	82° 39' 28.45	Estimated	21:1	NPI-P	N	No	No	NONE

Obstruction Data

	Close-in Obstruction	Displacement Distance	Slope	Controlling Obstruction	Marked/ Lighted	Height Above Runway	Distance From Runway	Direction From Runway End	Controllin g Offset
Primary Surface	No		21:1	TREES		65 ft	1,560 ft	Before Runway End	95 ft R
Runway End									
Marked Displaced Threshold									
Required Displaced Threshold									

Primary Surface and Safety Area

Object	Latitude	Longitude	Survey/ Estimate	Distance from Centerline	Direction from Centerline	Fixed by Height Function	Frangible	Marked	Aeronatical Study	Determination
--------	----------	-----------	---------------------	--------------------------------	---------------------------------	--------------------------------	-----------	--------	----------------------	---------------

Facility Name: Oak Tree Landing Airport

Inspection Date: 4/9/2026

Facility Type: Airport

Status: Active

Inspector: David Smith

Deficiencies

Inspection Date 4/9/26

Next Inspection 4/30/27

Deficiencies

09/27 : In accordance with Chapter 14-60.007(9)(f), FAC. – Hold position markings for paved taxiways shall be yellow.

Taxiway (A)

Taxiway A hold position markings at Runway 09 are faded and in poor condition.

09/27 : In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Taxiway (A)

Hold

Position

Taxiway A hold position markings black border is faded and in poor condition.

09/27 : In accordance with Chapter 14-60.007(9)(l)1., FAC. – Glass beads shall be required for all permanent pavement markings.

Taxiway (A)

Hold

Position

Taxiway A hold position marking at Runway 09 does not contain a sufficient amount of glass beads.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(d), FAC. – Threshold bars shall be white.

Runway 09 threshold bar is faded and in poor condition.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(b), FAC. – Runway designation markings shall be white.

Runway 09 runway designation markings are faded and in poor condition.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Displaced

Arrow Head

Runway 09 displaced threshold arrow head markings are not outlined with a black border six inches or greater in width.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(l)1., FAC. – Glass beads shall be required for all permanent pavement markings.

Displaced

Arrow Head

Runway 09 displaced threshold arrow heads do not contain a sufficient amount of glass beads.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Displaced

Bar

Runway 09 displaced threshold bar marking is not outlined with a black border six inches or greater in width.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(l)1., FAC. – Glass beads shall be required for all permanent pavement markings.

Displaced

Bar

Runway 09 displaced threshold bar does not contain sufficient amount of glass beads.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Runway

Centerline

Runway 09 runway centerline markings are not outlined with a black border six inches or greater in width.

Rwy End: 09 In accordance with Chapter 14-60.007(9)(l)1., FAC. – Glass beads shall be required for all permanent pavement markings.

Runway

Centerline

Runway 09/27 centerline markings do not contain a sufficient amount of glass beads.

Facility Name: Oak Tree Landing Airport**Inspection Date:** 4/9/2026**Facility Type:** Airport**Status:** Active**Inspector:** David Smith

Rwy End: 09 Runway Designation In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Runway 09 runway designation markings are not outlined with a black border six inches or greater in width.

Rwy End: 09 Runway Designation In accordance with Chapter 14-60.007(9)(l)1., FAC. – Glass beads shall be required for all permanent pavement markings.

Runway 09 designation markings do not contain a sufficient amount of glass beads.

Rwy End: 27 In accordance with Chapter 14-60.007(9)(b), FAC. – Runway designation markings shall be white.

Runway 27 runway designation markings are faded and in poor condition.

Rwy End: 27 Runway Centerline In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Runway 27 runway centerline markings are not outlined with a black border six inches or greater in width.

Rwy End: 27 Runway Designation In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Runway 27 runway designation markings are not outlined with a black border six inches or greater in width.

Rwy End: 27 Runway Designation In accordance with Chapter 14-60.007(9)(l)1., FAC. – Glass beads shall be required for all permanent pavement markings.

Runway 27 designation markings do not contain a sufficient amount of glass beads.

Rwy End: 27 Threshold Bar In accordance with Chapter 14-60.007(9)(l)2., FAC. – All markings on light colored pavements shall be outlined with a black border six inches or greater in width.

Runway 27 runway threshold bar marking is not outlined with a black border six inches or greater in width.

Rwy End: 27 Threshold Bar In accordance with Chapter 14-60.007(9)(l)1., FAC. – Glass beads shall be required for all permanent pavement markings.

Runway 27 runway threshold bar marking does not contain a sufficient amount of glass beads.

Mitigated Deficiencies

Rwy End: 09 In accordance with Chapter 14-60.007(2)(c)1.d., FAC. – For a runway that is paved, that is to be used by an aircraft that weighs greater than 12,500 pounds, and that has a visual landing approach: the approach surface ratio is 20:1.

Runway 09 approach surface ratio is 6:1 due to road 22 feet tall, 343 feet before the approach end of the runway, on centerline.

Runway 09 is displaced 100 feet.

Facility Name: Oak Tree Landing Airport

Inspection Date: 4/9/2026

Facility Type: Airport

Status: Active

Inspector: David Smith

License

Effective: 08/01/2026

Category: Public

Limitations: ☐ Day Use Only

Expires: 07/31/2027

☐ VFR Use Only

Conditions:

The department may revoke, refuse to allow or issue, any license or license renewal, if it determines that the airport does not comply with the conditions of the license, license renewal, or site approval or that the airport has become unsafe or unusable for flight operation due to physical or legal changes that were the subject of approval pursuant to Section 330.30(2)(e), F.S.

A. This Airport has the following landing areas and approach limitations.

1. Runway 09/27 is available for visual approaches only.

a. Runway 09 is FAR 77 category A(V).

b. Runway 27 is FAR 77 category A(V).

2. Runway 09 threshold is displaced 100 feet.

Additional Licensing Remarks: